

	OMSTRAP
BA 3220	High speed Automatic banding machine: Bundles a minute 35 with economic tape Standard arch 320 x 200 other measures if required Pneumatically adjustable tapes tensioning Use paper or polypropylene tapes 28 mm. With reduced thickness thanks to a system of air aspiration in the arch of launch. Banding start with photocell on the table, pedal or button. Pneumatic mechanical group of high reliability Control panel located on the operator side Standard voltage 220V monophase/50 Hz./0,5 Kw. Machine dimensions 600 x 500 x 1250 (L x P x H) Machine weight 70 Kg. Working table height 950 mm. Use compressed air 6 bar. Air consumption 10 liters for 30 cycles/minute Standard paper tape 28 mm thickness 90 grs. (70+20)/800 mt. standard film P.P. tape 28 mm. thickness 50 or 80 micron/1500 mt.
OPTIONAL Double press Start pedal Tape dimensions Arch dim. 30 mm. Tape dimensions Arch dim. 50 mm. Tape dimensions Arch dim. 77 mm. Tape dimensions Arch dim. 102 mm.	For special uses Recommended flying foot pedal safety standard CE 28 mm. Thickness on request 240x150/320x200/400x250/480x300/560-640-720-800-880-960x350 48 mm. Thickness on request 240x150/320x200/400x250/480x300/560-640-720-800-880-960x350 75 mm. thickness on request 240 x 150 / 320 x 200 100 mm spessori on request 240 x 150 / 320 x 200
	 BA 3220  BA 8035 P