


|  | OMSTRAP   |
|--|---|
| CS MD 450                                | <p>Semi-automatic taping machine that seals with self-adhesive tape the top and bottom of American-type boxes, in batches of set format, with easy and quick manual adjustment. The machine is particularly suitable for high, short or irregular shaped boxes and when combined with input and output roller conveyors it is a simple and inexpensive packing station.</p> <p>The cartons are moved by 2 lower plane drive belts and by 2 upper ones driven by a single motor. The adjustments for the various formats take place via handwheels</p> <p><b>manually adjustable format</b></p> <p>width from 180 to 450 mm.<br/> height from 180 to 480 mm.<br/> minimum length of 150 mm.<br/> machine with taping heads for adhesive tape with width of 50 mm.<br/> voltage V.220 monophase Hz.50, power installed Kw.0.40<br/> dimensions in plan view 1090 x 910 mm<br/> box transfer speed 20 metres/minute<br/> average production 1000 boxes/hour<br/> machine weight 100 Kg.<br/> work table height adjustable from 650 to 750 mm</p> |
| OPTIONAL                                 |   |
| Wheels<br>Loading roller<br>380 triphase | <p>4 table height wheels ranging from 750 to 820 mm<br/> Front and rear of 440 mm<br/> Voltage V.380 + N triphase Hz.50, power installed Kw.0.40</p>  |
|  |  <p>CS MD 450</p>   |