	OMSTRAP
CS MH 2A MINI 550	Auto-sizing automatic taping machine that seals with
H 75	auto-adhesive tape the top and bottom of American-type boxes of
	variable format. The machine combined with input and output
	conveyors is a simple and inexpensive packing station. The taping
	machine combined with automatic carton centring and spacing devices
	could also work in unmanned lines.
	The cartons are moved by 2 lower side drive belts driven by a single
	motor. The mobile parts are driven by pneumatic cylinders.
	auto-sizing for variable format with manual insertion
	width from 170 to 550 mm. (A)
	height from 75 to 550 mm. (C)
	minimum length of 180 mm. (B)
	Universal adhesive tape taping heads width 50 and 75 mm
	voltage V.220 monophase Hz.50, power installed Kw.0.40
	air consumption for N1 cycle. 1 at 6 BAR
	dimensions in plan view with guards 1155 x 920 mm
	belt translation speed 20m/minute
	machine weight 150 Kg.
	work table height adjustable from 650 to 750 mm without wheels
	colours ral blue 5013 grey 9006
OPTIONAL	
Wha alo	4 4-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-
Wheels	4 table height wheels ranging from 750 to 820 mm
Loading roller	Front and rear of 440 mm
380 triphase	Voltage V.380 + N triphase Hz.50, power installed Kw.0.40
Taping heads 50 Side barriers	Optional taping heads for adhesive tape only 50 mm
side parriers	Side panel guards
A	
	I III   I



CS MH 2A 550 H min 75 mm