

	<b>OMSTRAP</b>
<b>OMS 600</b>	<p>Patented <b>horizontal</b> strapping system for pallets:  Ideal for the fruit and vegetable market  Uses strap from 12 to 15 mm in diam. 200/280/406 optional 392  Raised platform for the application of the upper straps  Protective corners holder  Machine weight 120 Kgs.  Dimensions 1000x700x2500 (WxDxH)  <b>Maximum strapping height 2400 mm.</b>  <b>Minimum strapping height 150 mm.</b>  Wide wheels help to move the machine without effort  Strapper with a balanced weight to position the straps as needed.</p>
 <p><b>OMS 20</b></p>	 <p><b>OMS 600 + OMS 20</b></p>
<b>OMS 20 LT/13-16 mm</b>	<p><b>Standard automatic battery operated</b> strapping tool  <b>Uses polypropylene strap from 13 to 16 mm, thickness 0.5 –1.05</b>  <b>Uses polyester strap from 13 to 16 mm thickness 0.5-1.05</b>  Ideal for applying both vertical and horizontal straps  The strap is inserted through a single operation  Automatic tensing which can be regulated up to 2200 N  Vibration sealing  Weight of machine 3,6 Kg. including the battery  <b>Uses rechargeable 14,8V-2A/h LI-PO (lithium) batteries</b>  Dimensions: 140 X 290 X 165 mm. (W x L x H)  <b>made in Italy</b></p>