

SM 601 D + CS MH2AW 500

GFC 500

Loaded idler roller conveyors

Dimensions 400x500 with idler rollers for manual loading.

SM 601 D

Strapping machine for automatic line

Arch 850 x 600

External strap tensioning regulator from 5 to 45 Kgs.

Standard launching device

Polypropylene strap dimensions: 9/12 mm. thickness 060

Inside core 280 mm. (200 mm. by demand)

Working table height (fixed) 810 mm.

Standard voltage 220V mono-phase/50 Hz./0,9 Kw.

Overall dimensions (L x W x H) 1445 x 600 x 1540 mm.

Machine weight 220 kg.

CS MH 2AW 500

Automatic carton sealer for american type boxes

Size adjustable automatically

Width from 120 to 500 mm.,

Height from 120 to 500 mm.

Minimum length 210 mm.

The boxes are fed by side belts

Machine with head for sealing tape with width 50 and 75 mm universal

Tension V.380 three-phase Hz.50, power Kw.0,25

Overall layout dimensions mm.1090 x 890

Working table height mm 810 (with wheels)

Transfer box velocity 19 mt/minute

Medium production capacity 360 boxes/hour with double strapping and sealing

Machine weight 100 Kg

OPTIONAL

GRP/500/3

Unloaded extensible roller conveyors

small plastic wheels extension from 1200 to 4800 width 500

with fixed iron stop and wheels

