	OMSTRAP
WM WRAPALL A	Automatic closed table winding machine with:turntable diameter 1500 mm max capacity Kg. 2000base-hinged column to facilitate assembly/dismantlingdigital control electrical panelsoft start and indexed stop of the tableselection of digital lower/upper and separate revolutionsup down winding cyclephotocell for pallet height readingautomatic manual functiontable rotation speed adjustable from 0 to 10 rpmadjustable film reel speeddimensions of pallet that can be wrapped within table 800X1200X2100Hmax diameter of film reel that can be used 300 mm height 500 mmthickness of film from 12 to 35 micron (other thickness to be tested on the product)clutched roller cart for double section film draw adjustmentstandard voltage 220 V monophase power installed Kw. 1necessary system 220 V monophase power installed Kw. 1necessary system 220 V monophase power installed Kw. 1necessary system 220 V mono with thermal magnetic circuit breaker0.5 amps for industrial uselateral film reel for complete wrapping of pallet basemachine weight 600 Kg. colours ral blue 5013 grey 9006overall dimensions in plan view 2600X1500X2250H
OPTIONAL	packaging dimensions 1650X2250X800H wrapping cycle with weight for pallet cover top sheet insertion
WM WRAPALL AE WM WRAPALL AB	Model with electro-magnetic clutch Model with motorised pre-stretch
	WM WRAPALL A