

OMSTRAP

TR 1000x500 belt-driven	Length 1 m/width roller 500 mm/rollers diam. 48/fixed speed 15 m
TRC 1000x500 chain-driven	Length 1 m/width roller 500 mm/rollers diam. 48/fixed speed 15 m
TRCF 1000x500 friction-driven	Length 1 m/width roller 500 mm/rollers diam. 48/fixed speed 15 m
TR 2000x500 belt-driven	Length 2 m/width roller 500 mm/rollers diam. 48/fixed speed 15 m
TRC 2000x500 chain-driven	Length 2 m/width roller 500 mm/rollers diam. 48/fixed speed 15 m
TRCF 2000x500 friction-driven	Length 2 m/width roller 500 mm/rollers diam. 48/fixed speed 15 m

KEY

TR	there are various types of solution
TRC	roller and belt conveyor, capacity 30 kg
TRCF	roller and chain conveyor, capacity 50 kg
length	frictioned roller and chain conveyor, capacity 50 kg
width	various modules in one metre steps (1000-2000-3000, etc.)
height	570(480 max.) 720(630 max.) 870(780 max.)
speed	legs adjustable from 650 to 850 mm
motors	fixed speed 15 m/min.
standard rollers	HP 0.5
	rollers diameter 48 centre to centre distance 75/85

OPTIONAL

rollers diameter 32 centre to centre distance 55
surface heights upon request
speed upon request
guides and various accessories



**MOTORISED CURVED ROLLER
CONVEYOR**



MOTORISED ROLLER CHAIN CONVEYOR

