
	OMSTRAP
SM 702 NL in line	Automatic advanced 5/9 mm strapping machine in line:
	Strapping a minute single 31 packages a minute
	strap 5/9 inside core 200 external core 480 mm.
	Strap tensionig from 1 to 32 Kgs. adjustable
	Belt speed adjustable with inverter from 10 to 60 m/minute
	Automatic disobstruction and loop ejection
	Single strapping or transit function
	Change roll with automatic charge
	Working table height adjustable from 800 to 900 mm.
	Dimension products 120/450 x 10/400 x 210/500 (W x H x L)
	Max coils weight 25 Kg
	Standard voltage 380V triphase/50 Hz. 1,0 Kw
	Machine weight 460 Kg.
	Machine dimensions 1160 x 850 x 2300/2400 (L x P x H)
	Pneumatic double press 6 bar adjustable from 15 to 40 kg
	Air consumption 1,4 litre/cycle
	Opens wide for quick inspection and maintenance
	Security panels safety standard CE with press over 25 kg
	Managemet function with PLC SIEMENS
	Bright lamps for emergency signal
OPTIONAL	
	Energy saving with auto stand by
	Transit function for light packages
	Inside core roll 150 mm
	Pneumatic lateral squaring
	Working table height adjustable from 730 to 830 mm.
	Movement wheels
Bundle Flow	
L 850 J	





SM 702 NL in line