	OMSTRAP
SM 702 NS single	Automatic advanced 5/9 mm single strapping machine:
	Strapping a minute single 42 packages a minute
	Strapping a minute double 24 packages a minute
	strap 5/9 inside core 200 external core 480 mm.
	Strap tensionins from 1 to 32 Kgs. adjustable
	Belt speed adjustable with inverter from 10 to 60 m/minute
	Automatic disobstruction and loop ejector
	Photocells for sigle, double strapping or ransit function.
	Change roll with automatic charge.
	Working table height adjustable from 800 to 900 mm.
	Dimensions products 120/500 x 10/400 x 210 (W x H x L)
	Max coils weight 25 Kg
	Standard voltage 380V triphase/50 Hz. 1,0 Kw
	Machine weight 420 Kg.
	Machine dimensions 1230 x 660 x 2300/2400 (L x P x H)
	Pneumatic double press 6 bar adjustable from 15 to 25 kg
	Air consumption 1,1 litre/cycle
	Opens wide for quick inspection and maintenance
	Automatic strap tensioning control according to package dimension
	Equalization frontal doors
	Managemet function with PLC SIEMENS
	Bright lamps for emergency signal
OPTIONAL	
	Energy saving with auto stand by
	Transit function for light packages
	Inside core roll 150 mm
	Security panel safety standard CE with press over 25 kg
	Soft press for particular packages
	Pneumatic lateral squaring
	Working table height adjustable from 730 to 830 mm.
	Movement wheels



