	OMSTRAP
SM 702 Y	**Side-seal** equipped automatic strapping machine: **Close loop ejector** **Strap tensioning regulation with electromagnetical friction** **Automatic roll change from the outside** **over 60 strapping a minute sm 702 Y sm 702 Y-XLM** **over 35 strapping a minute sm 702 YA** Use strap 5,9,12 inside core 200 diam. external 480 mm. **Standard arch 600 x 650** Strap tensionig from 0 to 55 Kgs. Electronical regulation Adjustable sealing point from 445 to 645 mm Automatic disobstruction and close loop ejector Start with button on control panel side **Automatic roll change** **Roll truck inside** Minimun package dimension 70 x 80 mm (W x H) voltage 220V monophase/50 Hz./0,50 Kw. Machine dimensions 1448 x 670 x 1300 (L x P x H) weight 166Kg.
OPTIONAL	
SM 702 Y-XLM	**Side-seal without roller table of support**
SM 702 YA	In line version with photocells and motorized rollers
Pressa pn superiore	per pressatura superiore colli
Spintore pn laterale	per accompagnamento colli in battuta saldatore
Arches	Dimensionable if required with addictions of 200 mm.
PLC	Management with PLS siemens
Pedal	Start with **pedale a ciabatta**

archi WxH

400x650
600x650
600x850
600x1050
600x1250
800x850
800x1050
800x1250
1000x1050
1000x1250
1000x1650



SM 702 Y



SM 702 YA PRESS AND PUSHER

SM 702 YA