



## Advanced Packaging Systems Strong and reliable

### Dunnage-bags for load securement:

- Protects goods on any way of transport
- Simple to use
- Quick to inflate
- Safe to use and cost saving
- 100% recyclable
- ISO 9001 and AAR certified



### Available sizes

Size (cm)	Level	Max void size	Working pressure	Max working pressure	Type of transport
60 x 120	L1 AAR	25 cm	0,10 bar	0,20 bar	Intermodal
90 x 120	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
90 x 150	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
90 x 180	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
90 x 210	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
120 x 210	L1 AAR	50 cm	0,10 bar	0,20 bar	Intermodal
120 x 240	L1 AAR	50 cm	0,10 bar	0,20 bar	Intermodal

### Packaging details

Size	60 x 120	90 x 120	90 x 150	90 x 180	90 x 210	120 x 210	120 x 240
Art. nr.	AB00001	AB00002	AB00003	AB00004	AB00005	AB00006	AB00007
Nr. airbag/pallet	1050	900	800	675	620	440	420
Gross weight /pallet	295 Kg	330 Kg	353 Kg	351 Kg	369 Kg	344 Kg	369 Kg

Pallet size 100 x 120 x 110 cm




**OMSTRAP s.r.l.**

Capitale sociale int. Vers € 500.000  
Reg. Imprese Novara  
Cod. fisc. - P.I.V.A. 01931020034  
R.E.A. N° 205309 C.C.I.A.A. Novara

Sede : Via Borgomanero, 44 – 28045 Paruzzaro ( NO )  
Tel. 0322 541498 - Fax 0322 230064  
Stabilimento : Via Alfieri, 8 – 13876 Sandigliano ( BI )  
Tel. 015 691152 - Fax 015 691414  
e-mail : omstrap@omsspa.com

## Technical features


The OMSTRAP dunnage bags are made with a layer of strong polypropylene which protects the internal LDPE bladder.



The external PP layer is resistant to abrasions and adversities that may occur during the transport of goods.

The OMSTRAP dunnage bag is **100% recyclable**.

OMSTRAP airbags are ISO 9001 and AAR (American Association of Railroads) certified to guarantee the best performance and durability of use on overseas routes.



The dunnage bag valve, allows a quick inflation and deflation of the bag. The inflation tool is equipped with a «Venturi System» which allows the operator to recognize when the airbag has reached the right pressure.



Visit our website [www.omstrap.it](http://www.omstrap.it)