


	<b>OMSTRAP</b>
<p><b>SM 702 AH</b> <b>rulliere</b></p>	<p>Automatic roller conveyor machine with <b>motorized roller conveyors</b> with <b>high production capacity</b>:  standard arc 850x600 (W x H) maximum pack 800x550 (H)  <b>electronic tensioning strap 1 a 40 Kgs.</b>  <b>single, double or timed seating and transit only function</b>  <b>Strap loading and automatic reel change from the outside</b>  <b>Closed loop ejection in case of strapping without package</b>  Opening bookshelves for easy internal inspection  <b>roller speed from 15 to 60 m/min. adjustable with inverter</b>  HighTWorking Height Adjustable from 800 to900 mm . (optional 750/900)  <b>dimensione minima colli centrati 200 x 200 x 20 (L x W x H)</b>  Strapping conditions minimum parcel interval 200 mm  weight of 10 a 35 Kgs. packages (recommended press option for lower weights)  <b>productivity 18 packages/min with double parallel strapping</b>  <b>productivity 36 packages/min with single central strapping</b>  Diameter internal strap 200 mmcoil .  Strap used 5/9/12 mm  <b>HMI control panel located on the operator right side</b>  <b>Machine managed with Siemens PLC</b>  voltaggio standard 220 V monofase/50 Hz./1 Kw.  plan 1600(W) x 650(D) x 1397/1597  Machine weight 290 kg.  colour RAL Blue 5002 Grey 9006</p>
<div style="border: 1px solid black; padding: 10px; width: fit-content;"> <p><b>WxH bows</b></p> <p>850x800  1050x800  1250x600</p> </div>	<div style="text-align: center;">  <p><b>SM 702 AH</b></p> </div>