


	OMSTRAP
<b>SM 702 BH</b> <b>rugs</b>	<p>Automatic belting machine with <b>motorized mats</b> with <b>high production capacity</b>:</p> <p>standard arc 650x500 (W x H) maximum pack 600x450 (H)</p> <p><b>electronic tensioning strap 1 a 40 Kgs.</b></p> <p><b>single, double or timed seating and transit only function</b></p> <p><b>Strap loading and automatic reel change from the outside</b></p> <p><b>Closed loop ejection in case of strapping without package</b></p> <p>Opening bookshelves for easy internal inspection</p> <p><b>carpet speed from 60 m/min. adjustable with inverter 10 a</b></p> <p>HighTWorking Height Adjustable from 800 to 900 mm . (optional 750/900)</p> <p><b>dimensione minima colli centrati 130 x 120 x 20 (L x W x H)</b></p> <p>Strapping conditions minimum parcel interval 200 mm</p> <p>weight of 10 a 35 Kgs. packages (recommended press option for lower weights)</p> <p><b>productivity 20 packages/min with double parallel strapping</b></p> <p><b>productivity 40 pieces per minute with single central strapping</b></p> <p>Diameter internal strap 200 mm coil .</p> <p>Strap used 5/9/12 mm</p> <p><b>HMI control panel located on the operator right side</b></p> <p><b>Machine managed with Siemens PLC</b></p> <p>voltage standard 220 V monofase/50 Hz./1 Kw.</p> <p>Ingombro in plan 1400(W) x 650(D) x 1397/1950 with press (H)</p> <p>machine weight 250 kg.</p> <p>colour RAL Blue 5002 Grey 9006</p>
<div> <b>WxH bows</b>   550x500  650x500  850x600  850x800  1050x800 </div>	 <p><b>SM 702 BH</b></p>