


	OMSTRAP
SM 702 BPH carpets and press	<p>Automatic belt strapping machine with motorized mats and stabilizer tamper with high production capacity: arco standard 650x500 (W x H) pacco massimo 600x450 (H) electronic tensioning strap 1 a 40 Kgs. single, double or timed seating and transit only function Strap loading and automatic reel change from the outside Closed loop ejection in case of strapping without package Opening bookshelves for easy internal inspection carpet speed from 60 m/min. adjustable with inverter10 a Highworkingheight adjustable from 800 a900 mm . (optional 750/900) dimensione minima colli centrati 130 x 120 x 20 (L x W x H) Strapping conditions minimum parcel interval 200 mm weight of 10 a 35 Kgs. packages (recommended press option for lower weights) productivity 18 packages/min with double parallel strapping productivity 36 packages/min with single central strapping Diameter internal strap 200 mmcoil . Strap used 5/9/12 mm HMI control panel located on the operator right side Machine managed with Siemens PLC voltaggio standard 220 V monofase/50 Hz./1 Kw. Ingombro in plan 1400(W) x 650(D) x 1397/1950 with press (H) machine weight 250 kg. colour RAL Blue 5002 Grey 9006</p>
<div> WxH bows 550x500 650x500 850x600 850x800 1050x800 </div>	 <p>SM 702 BPH</p>