


	OMSTRAP
<p>GFC 500</p> <p>SM 601 DA</p> <p>CS MH 3AW 480</p> <p>OPTIONAL</p> <p>GRP/500/3</p>	<p>Roller conveyor with loading neutral measures 400x500 with idler rollers for preparation and manual loading</p> <p>Automatic strapping machine modified by line arch 850 x 600 70 Kgs strap tensioning. externally adjustable5 a automatic reel change Standard launch device and disconnection systems strap used 9 or 12 mm. polypropylene thickness 060 work table height. 810 mmpermanent internal strap coil diameter. (on request)280 mm200 mm Overall dimensions in plan mm. 1445 x 600</p> <p>Fixed format and line closure noping machine manually adjustable format and pneumatic flap closure unit width from 150 to 480 mm. (A) height from 120 to 480 mm. (C) length from 200 to 550 mm. (B) The cartons are dragged by means of side straps Universal adhesive tape taping heads width 50 and 75 mm Reel nastro adesivo da 330/660/990 m diam is max 280 mm voltage V.220 singlephase Hz.50, installed power Kw.0,40 Overall dimensions in plan mm.1650 x 980 Velocity transfer box 19 meters/minute average production 1000 boxes/hour machine weight 280 Kg. gestione sistema con PLC siemens</p> <p>Extensible unloading roller conveyor plastic castors extension from 48001200 a width 500 with fixed limit switch and wheels</p>
 <p>MODULO PER SCATOLE UGUALI</p> 