

Dunnage-bags for load securement:

- Protects goods on any way of transport
- Simple to use
- Quick to inflate
- Safe to use and cost saving
- 100% recyclable
- ISO 9001 and AAR certified



Avai	abl	e siz	es

				Max	
		Max void	Working	working	Type of
Size (cm)	Level	size	pressure	pressure	transport
60 x 120	L1 AAR	25 cm	0,10 bar	0,20 bar	Intermodal
90 x 120	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
90 x 150	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
90 x 180	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
90 x 210	L1 AAR	40 cm	0,10 bar	0,20 bar	Intermodal
120 x 210	L1 AAR	50 cm	0,10 bar	0,20 bar	Intermodal
120 x 240	L1 AAR	50 cm	0,10 bar	0,20 bar	Intermodal







Omstrap PPW Twin Bags

The safest and fastest system for filling large empty gaps



- Suitable for filling large gaps without the need for additional filling material.
- Recommended for empty spaces between 30 and 100 cm wide.
- Reusable and water resistant, with an extremely abrasion resistant outer PP layer.
- 100% recyclable

Size	Max. void size	Twin Bags/pallet
90x120 cm	60 cm	300 pcs/pallet
90x180 cm	70 cm	220 pcs/pallet
90x220 cm	70 cm	220 pcs/pallet
Pallet dimension	100x120x110cm	

Available sizes



Omstrap ECO Safety Sheets

- OMS Eco Safety Sheets are made up of a sturdy polypropylene barrier complete with straps already mounted, and ready for installation between the loading end and container doors.
- They prevent cargo from falling out when the container/truck doors are opened on arrival.
- OMS Eco Safety Sheets prevent the cargo damages, and they protect the safety of the operators during unloading of goods.
- They are easily assembled in less than three minutes

Materiali	100% Polipropilene riciclabile e riutilizzabile
Dimensioni	Larg. 220cm x Alt. 200cm
Peso	1,8 Kg/pz
Colore	Bianco
Resistenza	Cinghie da 50 mm, carico di rottura > 1.300 Kgf
Packaging	100 pz/box
Dimensioni box	100 x 120 x 65cm

Omstrap Lashing is the securing of transport cargo by means of strong polyester straps and steel buckles.

It applies to the transport of all types of goods: machines and vehicles, loading of packages on pallets, containers, etc. **Omstrap Lashing** is suitable to all ways of goods transport: trucks, vessels, containers, railroads.



LASHING STRAPS				
		BREAK STRENGTH	COIL LENGTH	
Cod. art.	WIDTH (mm)	(kgf)	(mt)	BAGS / PALLET
COLASH 105S	32	2.300	250	54
LASHING BUCKLES				
			LINEAR BREAK	
Cod. art.	DESCRIPTION	ТҮРЕ	STRENGTH	PIECES / BOX
COLF3030	For 32 mm	drop-forged	3.000	100