

## OMSTRAP


### SM 601 YA

**Side-seal** equipped automatic strapping machine:  
prepared with photocells for double strapping:  
**Close loop ejector**  
**Strap tensioning regulation with electromagnetical friction**  
**Automatic roll change from the outside**  
Strapping a minute 26 with launch device  
Standard arch 600 x 850 dimensionable if required  
Sealing point at 675 mm  
Roller working table adjustable from 485 to 585 (strapping from 510 to 610 )  
Strap tensioning from 7 to 70 Kgs. Electronical regulation  
Use polypropylene strap 9/12 mm. thickness 063 (advised)  
Disobstruction series RESET  
Working with pedal or button  
Inside Strap core 280 mm. (200 mm.if required)  
Mechanical group and arch completely in steel  
Control panel located on the operator side  
Standard voltage 220V monophase/50 Hz./1,2 Kw.  
Machine dimensions (L x W x H) 1485 x 616 x 1760 mm.  
Machine weight 220 kg.  
Safety standard CE  
Max package weight 100 Kg  
Minimum package dimension 130 X 20 (W x H)

### OPTIONAL

**SM 601 YAM inox**  
**SM 601 YA - XLM**  
**Arches**  
**Voltage**  
**PLC siemens**

**Stainless steel side-seal SUS 304 water flush washable**  
**Side-seal without roller table of support**  
Dimensionable if required with addition of 200 mm  
380 V triphase  
For electronical management



**SM 601 YA**



**SM 601 YAM**